
 شركة الكيماويات المتحدة United Chemicals Co.	<b>UNITED CHEMICALS COMPANY</b>		 سيدكو SIDCO
	<b>TECHNICAL DATA SHEET</b>		
	TDS No.: RD.TDS.054	Issue No.: 1.2	

## PRODUCT

# QUICKWAX

## HIGH QUALITY LIQUID FLOOR WAX

## PRODUCT DESCRIPTION

- QUICKWAX is a water-based high gloss, interlock and non-slippery floor polish.
- QUICKWAX is formulated to give a high quality, attractive and glossy floor polish.
- QUICKWAX can be used safely on all types floor. It eliminates dust accumulation, has good soil resistance and leaves no heel marks on floor.

## PHYSICAL PROPERTIES

Appearance:	Opaque liquid
Color:	White
Odor:	Acrylic
pH:	8 - 9
Specific Gravity @ 28°C:	1.025 – 1.035
Viscosity @ 28°C:	Not applicable
Solid Content:	30% min
Refractive Index:	1.3670 – 1.3807
Flash Point:	None
Toxicity:	None
Drying Time:	20 – 25 minutes
Gloss:	High gloss
Stability:	Stable for 3 years from production date

## INGREDIENTS

Water and Acrylic Polymer

## APPLICATIONS

- For the best results, initial application should be carried out on residue free and dry floor that had been stripped by REMWAX
- Apply QUICKWAX with a new and clean mop or applicator. Apply in smooth, thin coat, in any excess must be picked up and smoothed out. If second coat is required, wait for 30 – 40 minutes after the first coat depending on temperature and humidity conditions. Second coat must be applied perpendicular to the first coat's direction. Allow normally eight hours after application before buffing.

## STORAGE

Store the original container in cool and dry place away from food and feeding stuff.

## PACKING

4X4 L and 4x5 L

## PRECAUTIONS

Keep away from the reach of children.

Doc No.: RD-RDF-19	Issue No.: 1.0	Issue Date: 09.08.2015	Page 1 of 1
--------------------	----------------	------------------------	-------------

