
 شركة الكيماويات المتحدة United Chemicals Co.	UNITED CHEMICALS COMPANY		 سيدكو SIDCO
	TECHNICAL DATA SHEET		
	TDS No.: RD.TDS.060	Issue No.: 1.2	

PRODUCT

REMWAX

LIQUID FLOOR WAX REMOVER**PRODUCT DESCRIPTION**

- REMWAX is a very effective & latest development as stripper for metal interlock polymer acrylic floor finish. Formulated without ammonia.
- REMWAX is blended with alkaline medium & solvent that lifts emulsifies floor finish faster and effectively.

PHYSICAL PROPERTIES

Appearance:	Clear liquid, free from any impurities
Color:	Yellowish
Odor:	Mild solvent odor
pH:	13 – 14
Specific Gravity @ 28°C:	1.06 – 1.07
Viscosity @ 28°C:	Not applicable
Refractive Index:	1.3509 – 1.3645
Flash Point:	>100°C
Abrasive:	None
Stability:	Stable for 3 years from production date

INGREDIENTS

Water, Potassium Hydroxide, Sodium Silicate, Secondary Alcohol, Amphoteric Surfactant and Color

APPLICATIONS

Dilute REMWAX in hot water with 1:10 ratio. Apply it on the floor. Scrub floor surface with single disc or automatic scrubber vacuum machine with nylon abrasive floor stripping solution with wash mop or wet vacuum. Rinse floor with clean mop. Apply adequate rinse water to floor. Let dry till it is ready for new finish with Quickwax.

STORAGE

Store the original container in cool and dry place away from food and feeding stuff.

PACKING

4 X 4 L, 4 x 5 L and 30 L

PRECAUTIONS

Keep away from the reach of children

Doc No.: RD-RDF-19	Issue No.: 1.0	Issue Date: 09.08.2015	Page 1 of 1
--------------------	----------------	------------------------	-------------

